

Blue Tongue™ Two Way Aluminium Grid

Armstrong®
CEILING SOLUTIONS



BLUE TONGUE

Suspension Systems Content

Two Way Ceiling Systems Page 4

Axiom Perimeter Solutions Page 5

Axiom Pelmet Systems Pages 6 – 7



Blue Tongue™ Aluminium Grid

Armstrong® Blue Tongue™ Aluminium Grid Systems

Extruded aluminium grid systems are the natural complement to Armstrong acoustic ceiling panels in A-Grade commercial applications.

Armstrong Ceilings delivers more than 30 years of expertise in ceiling grid solutions to the Australian and New Zealand markets.

We offer a complete range of Modular, One Way and Two Way Systems, for both Mineral Fibre and Metal ceiling panels.

Key Features

- Full and rapid demountability and re-use of components
- Complete range of interlocking accessories
- Choice of module sizes, including 1200x1200, 1350x1350 and 1500x1500
- Engineered and tested system
- Complete integration with Perimeter/ Pelmet Systems

Technical Features

- Produced from proven 6063 T5 grade extruded aluminium
- Polyester Powdercoat
- Compliant to AS/NZS 2785:2020 – Suspended Ceiling Code

Axiom Perimeter Solutions

Armstrong Ceilings provides a comprehensive range of Axiom Perimeter Solutions, including: wall angles, transitions trims and pelmets.


Custom Ceiling Solutions

Armstrong Ceilings has the capacity of developing custom solutions to suit most commercial requirements.

For Seismic Design support please contact your local Armstrong Ceilings office.



Clean mitred cross runner intersection.



Armstrong® Blue Tongue™ positive lock connection.





3-sided Pelmet with Air Diffuser Face Plate

Two Way Ceiling Systems




NSW Police Ctr – Parramatta NSW



Two Way Exposed

Component Specifications



Item	Description	Dimensions (mm)			
		Slot Spacing	Length	Height	Width
BP4640037S37	Flat Faced 24mm Main Bar (Connection via M/R Joiner, item BP9338)	300	3600	38	24
BP4630037S38	Flat Faced 24mm Cross Runner	600	1200	38	24
BP4620037S30	Flat Faced 24mm Cross Runner Blue Tongue Connection – flush with Main Bar	–	600	38	24

Notes:

Other Flat Faced Tee profiles are available for custom modules
Details on Perimeters, Wall Angles and Accessories – refer page 9

System Drawing and Installation


(Typical modules are 1200 x 600mm and 600 x 600mm).



Standard lay-in installation of Blue Tongue Aluminium 24mm Grid with Square or Tegular edge panels.

Key Features


- Practical and simple
- Full accessibility to plenum
- Simple removal of panels
- Best ceiling longevity with lowest maintenance costs



AXIOM Perimeter Solutions and Accessories


Perimeter / Transition Trims / Wall Angles

Suitable for all Systems




Item No.	ALPT4500LL	ALPTQLFF45	ALBULK3600SW	ALPTPERFTH3600	ALPTFF	ALPT3600PB
Description	Top Hat with 70mm Upturn	Flat Face	Bulk Head Trim	Perforated Top Hat	Flat Face with Horizontal Leg for 13 PB	Top Hat with Horizontal Leg for 13 PB
Dimensions (mm) (l) x (h) x (w)	4500 x 70 x 41	3600 x 45 x 24	3600 x 38 x 28	3600 x 38 x 45.5	3600 x 45 x 32	3600 x 45 x 32

Only suitable for Modular Ceiling Systems




Suitable for all Systems




Item No.	ALMRTH3600OS	ALMRTH4050OS	ALMRTH4500OS	ALO09RCPSW	ALO08RCPSW
Description	Top Hat Punched one side @ 1200cc.	Top Hat Punched one side @ 1350cc.	Top Hat Punched one side @ 1500cc.	Shadow line Suits roll in clip ALRIC	Std "L" Suits roll in clip ALRIC
Dimensions (mm) (l) x (h) x (w)	3600 x 45 x 32	4050 x 45 x 32	4500 x 50 x 32	3600 x 29 x 29	3600 x 24 x 20

Perimeter Trims / Accessories for One Way MetalWorks Hook On System



Item No.	ALPTONEWAYSW	ALPTHO	ARM-037	ARM-035	ARM-034	ARM-033
Description / Application	Perimeter Trim	Top Hat Hook On Plasterboard Perimeter	Perimeter Trim Joiner Grub screw fastening	Main Runner Joiner To suit ALOWTHMR	Roll In Clip Connects Main Runner to Perimeter Trim	Roll In Clip Connects Locking Spline to Perimeter Trim
Dimensions (mm)	600 x 50 x 25	3600 x 50 x 35				

Accessories for Modular, One Way (for Mineral Fibre) and Two Way Systems



Item No.	ALRIC	ALMRJL*	ALMRJL90	ALRICL	ALSDL / ALSDS	ALSCLH
Description	Roll In Clip Small	Main Bar Joiner	90 Degree Bracket	Roll in Clip Large	ALSDL: Long grub screw-driver ALSDS: Small grub screw-driver	Suspension Clips
Application of Accessory Item	Connects all sections with all wall angles and Perimeter Trims / Pelmet	Connects all Main Bars: 45 and 50mm sections *M/R Joiner for Two Way System is BP9338	Used with all Main Bars 45 and 50mm sections	For connecting Main Bars or Cross Runners to Perimeter Trims	For use with Grub screw Roll in Clip	For use on all Main Bars and Perimeter Trims

AXIOM Pelmet Systems



3-Sided Pelmet with slotted Air Diffuser Face Plate – Modular Grid and Ultima panel — Woolworths HQ, Sydney


Transition in style

Regain aesthetic control of the perimeter with an Armstrong® Axiom Pelmet Systems. The transition from pelmet to either plasterboard margin or acoustic ceiling is now simple. Armstrong® Axiom Pelmet Systems are a pre-engineered solution, integrating curtain pelmets, air distribution and ceiling elevation changes. Field fabrication and on-site decisions become a thing of the past. Armstrong® Axiom Pelmet Systems directly integrate with the ceiling grid via a positive locking connection clip. Concealed splice plates enable mechanical lock connections between adjacent pelmet sections.

Three easy Profiles

There are three basic aluminum extrusion profiles that provide a precise, crisp architectural detail.


1




2-Sided Pelmet with transition to Acoustical/Drywall Grid

Single piece aluminium extrusion that forms a simple 2 sided pelmet. Transition to either acoustical grid or set plaster margin.

2




3-Sided Pelmet with transition to Acoustical/Drywall Grid



Pelmet with Extension

Pre-engineered aluminium 3 sided pelmets can be produced from one or two piece sections enabling flexibility in size of pelmet. Extension components allow for additional design flexibility and ceiling elevation changes. Transition to either acoustical grid or set plaster margin.

3



3-Sided Perimeter Pelmet with Diffuser Face Plate and transition to "Blue Tongue" Grid

Pelmets can be designed for full integration with air distribution at the perimeter. Diffuser face plate is pre-slotted according to air supply specifications. Transition to either acoustical grid or set plaster margin.

AXIOM Pelmet Systems



Three-Sided Pelmet with Air Diffuser Face Plate



Two Piece Pelmet with Margin

Accessories for Axiom Pelmet Sections


Component Specifications



Item	Design
ALMRJS	Joiner for Pelmet



Single Piece Pelmet



One Way System with Composite Pelmet

Additional information and detailed drawings on the Axiom Pelmet Systems can be found at www.armstrongceilings.com.au



For Seismic Design support please contact your local Armstrong Ceilings office.

Distributed by



GrayKing Interior Supply

📞 NSW (02) 9666 6688
 QLD (07) 3267 6222
 ✉️ sales@grayking.com.au
 🌐 grayking.com.au



Madex Linings & Ceiling Distributors

📞 VIC (03) 9336 2419
 ✉️ info@mlcd.com.au
 🌐 mlcd.com.au



M & C Plaster Supply

📞 VIC (03) 9362 0214
 ✉️ info@mcplaster.com.au
 🌐 mcplastersupplies.com.au