

PeakForm Suspension Systems


Distributed by



PEAKFORM SUSPENSION



The PeakForm Range: Where Innovation meets Performance

 **PeakForm** is a comprehensive range of suspended ceiling grid solutions designed to meet most commercial design requirements:

- General Application: Including PRELUDE XL² 24mm and SUPRAFINE XL² 15mm Tee Grid systems.
- Designer Applications: Including the minimalist SILHOUETTE 15 XL² Steel Exposed Slotted Grid.

Axiom Perimeter Solutions

PeakForm Grid Systems are made complete with a Comprehensive range of Axiom Perimeter Solutions, including: Wall angles, Trims, Transitions, Pelmet and Accessories.

PeakForm Grid Profiles

PeakForm is an innovative design for Main Bars and Cross Runners. The taller **PeakForm** profiles are engineered to create a stronger, more stable suspension system making installation both faster and easier.

PeakForm Main Bars feature a firm, quick and easy assembled Main Bar to Main Bar / bulb to-bulb connection.

The staked-on Superlock joiner clip allows for Main Bars to be disconnected and reconnected laterally in low clearance areas or in the middle of a room. Superlock is an industry first staked-on clip for Main Bars which provide tighter, secure bulb-to-bulb connections; connections are confirmed by an audible click.



Thin gauge technology

A lighter carton weight enables easier handling on site, plus the added benefit of the **PeakForm** bulb allows easy cutting of the grid.



Physical detail

All grid sections are made from double-web galvanised steel with a surface finish of baked polyester paint.

Rotary Stitched for strength


All **PeakForm** components feature a unique “rotary stitched” construction. The two metal layers of the vertical web are mechanically locked together in a sophisticated in-line process. Stitching enhances the torsional resistance and general “feel” of the **PeakForm** components.



PeakForm “click” installation

PeakForm Cross Runners in both 24mm and 15mm widths feature an advanced stab system that locates with an audible “click”, ensuring a solid installation at all times. The “stab” end details are precision stamped from a separate piece of high grade steel providing increased accuracy and speed of installation.

Cross Runners are inserted to the right of each other through the Main Bar slots and easily pushed home.



Sustainability


Armstrong **PeakForm** suspension systems contain 25% recycled content and can be fully recycled at the end of life.

PeakForm grid systems are modular and can be disassembled and reused.

PeakForm suspension systems meet the requirements of Australian Standard AS/NZS 2785:2020 “Suspended Ceilings Design and Installation” and are designed for use with a wide variety of Armstrong ceiling products including: mineral and soft fibre, metal, wood and special solutions.

Compliant with Australian & New Zealand Standards

PeakForm suspension systems meet the requirements of AS/NZS 2785:2020 “Suspended Ceilings Design and Installation” and are designed for use with a wide variety of Armstrong ceiling products including: mineral and soft fibre, metal, wood, plasterboard and other special panels.




For Seismic Design support please contact your local Armstrong Ceilings office.

PeakForm Prelude 24 XL²



PeakForm PRELUDE 24 XL² suspension system is a robust, general purpose, exposed 24mm “tee” grid, suitable for square edge and tegular edge ceiling panels.


Main Bar: PRELUDE 24 XL² with Superlock Clip (bulb-to-bulb connection)



Item Number	Dimensions length (mm) height (mm) width (mm)			Rout Centres mm	Content / Carton pcs lm		Weight / Carton kg
73 40 42	3600	43	24	100	20	72	22
BP 73 40 42 BL*	3600	43	24	100	20	72	22

* Black Pre-painted Capping


Cross Runner: PRELUDE 24 XL² (stab system, override)



Item Number	Dimensions length (mm) height (mm) width (mm)			Rout Centres mm	Content / Carton pcs lm		Weight / Carton kg
HBP 31 30 52	1200	35	24	300	60	72	21
BP 31 30 52 BL*	1200	35	24	300	60	72	21
HBP 31 20 22	600	30	24	–	60	36	10
BP 31 20 22 BL*	600	30	24	–	60	36	10


* Black Pre-painted Capping

Section Drawings




System Drawing and Installation (Typical modules are 1200 x 600mm and 600 x 600mm. Special sizes available upon request.)

Standard lay-in installation of 24mm exposed suspension system using Board or Tegular tiles.




Perimeter Trims and Accessories

Perimeter Trims




HBPT1932H

Steel




HBP 784003

Steel




AL009RCPGW

Aluminium




AL008RCPGW

Aluminium



ALBULK3600GW


Aluminium



ALSWA1



ALSWA4




ALSWA6


Aluminium

Item Number	Description	Length (mm)	Cont / Cart'n pcs	Wt / Cart'n kg
Steel Perimeter Trims: Roll Formed and Prepainted				
HBPT1932H	Long Leg Wall Angle	3600	30	21
HBP784003	Shadow Line Wall Angle	3600	30	20
7800PBL	Wall Angle (Black) 22x22mm	3600	30	20
Aluminium Perimeter Trims: Extruded and Powdercoated				
AL008RCPGW	Wall Angle for Roll In Clip Attachment	3600	20	14
AL009RCPGW	Shadow Line Wall Angle for Roll In Clip Attachment	3600	20	14
ALBULK3600GW	Bulkhead Trim (suits both 10mm and 13mm Pb)	3600	6	6
ALSWA1	Heavy Duty Aluminium Wall Angle	3600	20	17
ALSWA4	Heavy Duty Aluminium Shadow Line Wall Angle	3600	20	23
ALSWA6	Seismic Aluminium Shadow Line Wall Angle	3600	20	27.5


Suspension & Accessories



SCPF




ARM-051




Trclip and threaded rod/nut

BPDW10LTG90
BPDW13LTG90
BPDW16LTG90



ALRIC

Item Number	Description	Length (mm)	Cont / Cart'n pcs	Wt / Cart'n kg
SCPF	Hook Suspension Clip for 5mm Rod	165	100	2.2
ARM-051	Direct Fix Clip	175	100	2.6
Trclip	Suspension Clip for 6mm Threaded Rod	80	100	2.0
M6 Rod	6mm Threaded Rod	1200	50	11.0
M6 Nuts	6mm nuts for Threaded Rod	-	200	0.4
BPDLC	Direct Load Ceiling Clip	80	250	5.5
BPUHDCA	Universal Hold Down Clip	-	1000	4.0
ALRIC	Roll In Clip	65	100	5.0
ROD 5mm	5mm Suspension Rod	4000	40	24.2
SR2536	2.5mm Suspension Wire	3600	160	25.0
188	Angle Bracket	47 x 47	100	1.2
247	Suspension Rod Angle Bracket	55	100	2.1
274	Suspension Rod Bracket	80	100	2.1
254	5mm ROD joiner spring adjustable	-	100	0.9
HBPGM1249	Expansion Sleeve to suite 24mm grid	100	100	5.0
BPDW10LTG90	Drywall Transition Clip suits 10mm Plasterboard	-	200	11.0
BPDW13LTG90	Drywall Transition Clip suits 13mm Plasterboard	-	200	11.0
BPDW16LTG90	Drywall Transition Clip suits 16mm Plasterboard	-	200	11.0
GPGW	Grid Touch Up Paint (128g net)	-	6	1.3
DWDFC120	120mm L Shape	120	100	5.0
DWDFC	180mm L Shape	180	100	6.5



BPUHDCA




188



247




TOUCH UP PAINT



DWDFC

DWDFC120




BPDLC



274



254





HBPGM1249



Perimeter Solutions

Perimeter Detailing Recommendations



Square Edge Panels



Grid, Wall Angle and "Square Edge Panel" at same level





Grid, Wall Angle and "Square Edge Panel" at same level





Tee Bar is secured to Wall Angle via Roll In Clip

Note: Wall Angles should be fixed to wall at 450mm centres



Tegular Edge Panels





Panel edge is field "tegulated" at Wall Angle



Wall Angle position is dropped to level of face of Panel; Tee Grid is packed at Wall Angle and Panel is square cut at wall angle





Panel edge is field "tegulated" at Wall Angle



Wall Angle position is dropped to level of face of Panel; Tee Grid is packed at Wall Angle and Panel is square cut at wall angle

For information on Blue Tongue Aluminium Grid and Axiom Perimeter / Pelmet systems, refer to the following brochures.



Specifications

Scope

The contractor to furnish all materials, labour and equipment for the erection of the exposed ceiling system where so indicated on the architectural drawings.

Material

Ceiling suspension shall be Armstrong PeakForm two way exposed, hot dipped galvanised steel system; (either): Prelude XL² 24mm Tee, SupraFine XL² 15mm Tee, or Silhouette XL² 15mm Steel Exposed Slotted "shadowline hat" profiles. All materials supplied by Armstrong meet the requirements of Australian Standard AS/NZS 2785:2020 "Suspended Ceilings Design and Installation".

Perimeter Detail

Wall Angles should be fixed to wall at 450mm centres. Exposed ceiling grid members intersecting with the Wall Angle or Shadowline Wall Angle, may either be unfixed, or fastened with a Roll In Clip.

Installation

The Main Bar shall be hung with a 5mm galvanised rod and clip system or 2.5mm wire, accurately levelled. Suspension points shall be spaced at 1200mm* centres along the Main Bar. Cross Runners shall intersect and be positively locked to Main Bars. Panel Hold Down Clips to be used as required. Hangers, Main Bars and Cross Runner shall be spaced so as not to exceed the design ceiling load or as may otherwise be required to prevent deflection in excess of 1/360 of the span of the spacers or Main Bars. Where light fittings, air conditioning fixtures etc are to be supported by the grid system, extra hangers may be required. Down bracing to be incorporated in ceiling systems when used externally or adjacent to opening prone to sudden uplift caused by external wind forces.

* For suspension points greater than 1200mm centres along the Main Bar, contact your local Armstrong representative for load ratings.

Suspension & Accessories

Main Bar to Main Bar (Fixture / Panel Orientation)

Main Bar Cross Runner x 600 Cross Runner x 1200				
1. FIXTURE* (mm)	1200 x 600	600 x 600	1200 x 300	600 x 600
2. PLANNING MODULE (mm)	1200 x 1200	1200 x 1200	1200 x 600	1200 x 600
3. HANGER SPACING (mm)	1200	1200	1200	1200
Max Fixture Weight (kgs)				
4. PRELUDE 24	21.2 kg	14.0 kg	17.4 kg	14.0 kg
5. SUPRAFINE 15	27.9 kg	13.9 kg	24.9 kg	13.9 kg
6. SILHOUETTE 15	-	-	-	14.2 kg

Cross Runner to Cross Runner (Fixture / Panel Orientation)

Main Bar Cross Runner x 600 Cross Runner x 1200				
1. FIXTURE* (mm)	1200 x 600	600 x 600	600 x 600	1200 x 300
2. PLANNING MODULE (mm)	1200 x 1200	1200 x 1200	600 x 600	1200 x 1200
3. HANGER SPACING (mm)	1200	1200	1200	1200
Max Fixture Weight (kgs)				
4. PRELUDE 24	10.6 kg	10.6 kg	37.5 kg	17.4 kg
5. SUPRAFINE 15	-	-	37.3 kg	-
6. SILHOUETTE 15	-	-	37.9 kg	-

Connection Strength (SEISMIC)

Main Bar
HBP734042

Minimum KGS to Pull Out
Compression / Tension
174 kg / 133 kg

Cross Runner
All Cross Runners exceed 136 kg in both compression / tension.

Loading Parameters

- Main Bars at 1200mm centres
- Cross Runners 1200mm at 600mm spacing
- Suspension points spaced at 1200mm on Main Bar

***Note:** Additional independent support of heavy fixtures should be considered for safety purposes.

The above data is based on 1200mm hanger spacing, board weight of 4.8kg/m², maximum deflection of tees not to exceed 1/360 of the span and suspension system installed in accordance with AS/NZS 2785:2020.

Contact us

NSW

📍 65A Stephen Road
Botany New South Wales 2019
☎ (02) 9666 6688
✉ sales@grayking.com.au

QLD

☎ (07) 3267 6222
✉ sales@grayking.com.au

Distributed by



Grayking Interior Supply Pty Ltd

sales@grayking.com.au
www.grayking.com.au