martini
Prime

Martini Prime is a thermally-bonded polyester fibre insulation specifically designed to increase the acoustic and thermal characteristics of high performance plasterboard, masonry and aerated concrete composite wall systems. Designed for use in apartment walls and ceilings where very high standards of acoustic performance are mandatory.

Available in rolls, Martini Prime is non-itch and doesn't required any protective clothing or masks during installation.

Application

- High performance partition wall cavity infill for residential apartments
- Suspended ceilings

Fire Resistance

Test method	The following results were obtained when CSR Martini product was subjected to early fire hazard testing in accordance with Australian Standards AS 1530.3.
Results	Ignitability 0 Spread of Flame 0 Heat Evolved 0 Smoke Developed 0-1

Environmental benefits

Martini Prime is manufactured from thermally-bonded polyester fibre with up to 80% recycled fibre content from post-consumer PET packaging, such as empty drink bottles.

- No chemicals or resin binders are used in manufacture
- Odourless
- No waste is generated in manufacture
- No water or ozone-depleting gases are used in manufacture
- No chlorides are present in the product
- Suitable for use in Green Star™ projects

Specification Table

Product	Thickness (mm)	Roll width (mm)	Roll length (m)	Pieces per pack	m2 per pack	Product Code (Black)
Prime 30	30	610	20	2	18.3	130513
Prime 50	50	610	15	2	18.3	130514
Prime 65	65	610	10	2	12.2	130515
Prime 75	75	610	10	2	12.2	130516
Prime 100	100	610	7	2	8.54	130517

Distributed by

GRAYKING INTERIOR SUPPLY

Acoustic performance

Sample system 1

Rw 61, Rw + Ctr 50*

Two rows of 64mm decoupled steel studs set in separate tracks separated by 20mm gap with two layers of 13mm Gyprock Fyrchek to each external face with Martini Prime 50 fitted into one cavity.

Sample system 2

Rw 62, Rw + Ctr 50*

One layer of 13mm fire rated plasterboard fixed to 28mm furring channel, 75mm Hebel Powerpanel, 35mm gap, 64mm steel studs, 1 layer 13mm Gyprock Fyrchek, Martini Prime 30 in 28mm furring channel gap and Martini Prime 75 in the steel stud cavity.

Distributed by

martini
Prime

Distributed by

Grayking
Interior Supply

NSW
65A Stephen Road
Botany New South Wales 2019
(02) 9666 6688
sales@grayking.com.au

QLD
(07) 3267 6222
sales@grayking.com.au

grayking.com.au