

Nova White

Nova White is a 9mm white lay-in ceiling tile incorporating a High Density board with PVC laminate face and foil backing. The low sheen fine textured laminate facing reduces the visibility of blemishes and provides an easy surface to clean while the foil backing provides a condensation barrier limiting the possibility of tile sag and discoloration.

Nova White is suitable for commercial and retail applications where humidity or low ventilation roof spaces may be an issue.

ADVANTAGES

- High quality laminate
- Ease of maintenance
- Improved sagging performance
- Low sheen finish

PERFORMANCE DETAILS

Nova White was subjected to test procedures described in AS/NZS 3837:1998 'Method of test for heat and smoke release rates for materials and products using an oxygen consumption calorimeter' for the purpose of determining the Group classifications in accordance with:

- National Construction Code (NCC) volume one specifications C1.10 and A2.4 of the Building Code of Australia (BCA).
- Fire tested to achieve the least fire hazard Group Number for ceiling materials as defined by BCA BRANZ assessment No. FH 5205.



BOARD SPECIFICATION

Feature	Description
Thickness	9mm
Sheet Size (width x length)	595 x 1192mm
Edge	Square edge
Packaging	6 Tiles per pack
Weight	5.30kg per unit 7.00kg per m ² (nominal)
Colour	Matt finish (low sheen fine textured)
Grid	Exposed
Finish - Face	PVC laminate
Finish - Back	Foil backing
Core	High density Gypsum core
Fire Hazard Properties	Group 1 - in accordance with BCA Specification C1.10a Fire Hazard Properties - Floors, Walls and Ceilings
Combustibility	Non Combustible material as defined in BCA Deem-to-Satisfy Provisions C1.12
VOC	Less than 0.5mg/m ² /hr
GECA	N/A

Distributed by



www.grayking.com.au



WASTE MANAGEMENT

Waste collection services are available to divert acceptable plasterboard waste away from land fill for recycling or re-processing for other uses. For information on waste collection services available, please contact your local USG Boral office.

VOLATILE ORGANIC COMPOUNDS (VOC) AND FORMALDEHYDE MINIMISATION

USG Boral Nova White has been independently tested to confirm compliance with Green Star specification limits for VOCs and formaldehyde. Emission Test Certificate CV130506.

REFERENCES

Refer www.usgboral.com/novawhite for Material Safety Data Sheet, Volatile Organic Compound Emission details and Fire Test Report information. For Ceiling Tile range, refer to www.usgboral.com/ceilings

Distributed by



Grayking Interior Supply Pty Ltd

NSW

📍 65A Stephen Road
Botany New South Wales 2019
☎ (02) 9666 6688
✉ sales@grayking.com.au

QLD

☎ (07) 3267 6222
✉ sales@grayking.com.au

www.grayking.com.au

© 2014 USG BORAL. All rights reserved. The trademarks USG BORAL, INNOVATION INSPIRED BY YOU and TecASSIST are trademarks of USG Boral Building Products or one or more of its affiliates.

This technical information is intended to provide general information on plasterboard products and should not be a substitute for professional building advice. We recommend you use a qualified person to install USG Boral plasterboard. Illustrations in this guide are only representative of USG Boral plasterboard products and the appearance and effects that may be achieved by their use. To ensure the information you are using is current, USG Boral recommends you review the latest building information available on the USG Boral website. www.usgboral.com

USG Boral Building Products Pty Limited – ABN 84 004 231 976
251 Salmon Street, Port Melbourne, Vic. 3207

BCC 13089 10/2014