



DATA SHEET MINERAL FIBRE




Brillianto A 15mm

Order code	Edge	Size	Each/carton
160094	SQ	1200 x 600 x 15mm	10
160095	SQ	600 x 600 x 15mm	12



SQUARE EDGE (SQ)

Sound Absorption Value



Freq. [HZ]	Suspension depth E200 α_p
125	0.55
250	0.80
500	0.90
1000	0.85
2000	0.95
4000	1.00
NRC	0.90
α_w	0.90
SRA	0.95

Weight	Approx 4.2kg/m ²
Fire Resistance	Achieves Group 1 Fire Rating in accordance with AS5637.1:2015
Light Reflection	Approx 78 (ISO 7724-2, ISO 7724-3)
Cleanroom Class	Up to ISO 5 (ISO 14644-1:1999)
Recycled Content	This tile is 100% recyclable and is manufactured with up to 54% recycled content
Green Certification	Level A Ecospecifier Global Greentag Certification
Warranty	Up to 30 Years when used in conjunction with Rondo Duo Exposed Steel Grid. Please see our warranty for full details
Care and Maintenance	OWA Mineral Fibre Acoustic Tiles are manufactured using the wet-felt process according to DIN18177 which means that by design, less dirt is trapped in the ceiling panel. However, if cleaning is required tiles can be vacuumed or wiped with a damp cloth soaked in clean water

Distributed by



Grayking Interior Supply Pty Ltd

NSW

65A Stephen Road
Botany New South Wales 2019
(02) 9666 6688
sales@grayking.com.au

QLD

(07) 3267 6222
sales@grayking.com.au

www.grayking.com.au

