



## DATA SHEET MINERAL FIBRE




### Sinfonia Balance

Order code	Edge	Size	Each/carton
196969	SQ	1200 x 600 x 20mm	8
196970	SQ	600 x 600 x 20mm	10
197061	SLT	1200 x 600 x 20mm	8
197062	SLT	600 x 600 x 20mm	10



### Sound Absorption Value



Freq. [HZ]	Suspension depth E200 $\alpha_p$
125	0.45
250	0.50
500	0.80
1000	1.00
2000	1.00
4000	1.00
NRC	0.80
$\alpha_w$	0.80
SRA	0.95

<b>Weight</b>	Approx 4.4kg/m <sup>2</sup>
<b>Fire Resistance</b>	Achieves Group 1 Fire Rating in accordance with AS5637.1:2015
<b>Light Reflection</b>	Approx 87 (ISO 7724-2, ISO 7724-3)
<b>Cleanroom Class</b>	Up to ISO 5 (ISO 14644-1:1999)
<b>Recycled Content</b>	This tile is 100% recyclable and is manufactured with up to 32% recycled content
<b>Green Certification</b>	Level A Ecospecifier Global Greentag Certification
<b>Warranty</b>	Up to 30 Years when used in conjunction with Rondo Duo Exposed Steel Grid. Please see our warranty for full details

### Care and Maintenance

OWA Mineral Fibre Acoustic Tiles are manufactured using the wet-felt process according to DIN18177 which means that by design, less dirt is trapped in the ceiling panel. However, if cleaning is required tiles can be vacuumed or wiped with a damp cloth soaked in clean water

Distributed by



**Grayking Interior Supply Pty Ltd**

#### NSW

65A Stephen Road  
Botany New South Wales 2019  
(02) 9666 6688  
sales@grayking.com.au

#### QLD

(07) 3267 6222  
sales@grayking.com.au

www.grayking.com.au

