



DATA SHEET MINERAL FIBRE




Sinfonia Privacy

| Order code | Edge | Size | Each/carton |
|------------|------|-------------------|-------------|
| 164980 | SQ | 1200 x 600 x 20mm | 8 |
| 450429 | SQ | 600 x 600 x 20mm | 8 |



Sound Absorption Value



| Freq. [HZ] | Suspension depth E200 α_p |
|------------|----------------------------------|
| 125 | 0.50 |
| 250 | 0.75 |
| 500 | 0.80 |
| 1000 | 0.80 |
| 2000 | 0.90 |
| 4000 | 0.90 |
| NRC | 0.85 |
| α_w | 0.85 |
| SRA | 0.85 |

| | |
|----------------------------|---|
| Weight | Approx 6.4kg/m ² |
| Fire Resistance | Achieves Group 1 Fire Rating in accordance with AS5637.1:2015 |
| Light Reflection | Approx 87 (ISO 7724-2, ISO 7724-3) |
| Cleanroom Class | Up to ISO 5 (ISO 14644-1:1999) |
| Recycled Content | This tile is 100% recyclable and is manufactured with up to 32% recycled content |
| Green Certification | Level A Ecospecifier Global Greentag Certification |
| Warranty | Up to 30 Years when used in conjunction with Rondo Duo Exposed Steel Grid. Please see our warranty for full details |

Care and Maintenance

OWA Mineral Fibre Acoustic Tiles are manufactured using the wet-felt process according to DIN18177 which means that by design, less dirt is trapped in the ceiling panel. However, if cleaning is required tiles can be vacuumed or wiped with a damp cloth soaked in clean water

Distributed by



Grayking Interior Supply Pty Ltd

NSW

65A Stephen Road
Botany New South Wales 2019
(02) 9666 6688
sales@grayking.com.au

QLD

(07) 3267 6222
sales@grayking.com.au

www.grayking.com.au

