



Timbertop Slat Panel

FilaSorb™ 30

acoufelt
making quiet

Distributed by



Product Detail

Product	Timbertop Panel
Surface	Wall and ceiling
Composition	Polyester + MDF + Non PVC finish
Material	FilaSorb™ Acoustic Panel
Recycled content	60% min
Dimensions	1200 x 2800mm Custom sizes available
Thickness	34mm +/- 10% 42mm +/- 10%

Guarantees

Warranty against defects	20 Years*
Light fastness warranty	20 Years*
*conditions apply	

Distributed by



NSW
65A Stephen Road
Botany New South Wales 2019
(02) 9666 6688
sales@grayking.com.au

QLD
(07) 3267 6222
sales@grayking.com.au

Technical Data

Indoor Air Quality	SCS-EC10.3-2014 v4.0 meeting standard CDPH/EHLB Standard Method v.1.2-2017, ~ 0.5mg /m ³	
Light Fastness	ISO 105-B02 1994, 6-7	
Fire Test Method	CORE	FACING
34mm	AS ISO 9705 – Group 1, SMOGRA – 5.8m2/s2	AS ISO 9705 – Group 3
42mm	AS ISO 9705 – Group 1, SMOGRA – 5.8m2/s2	AS ISO 9705 – Group 2


Environmental Attributes

- Recognised under LEED
- Minimum 60% recycled PET



Acoustic Performance

Sound Absorption	ISO 354-2006 NRC 0.80 (no air gap) NRC 0.95 (20mm air gap)
------------------	--




Frequency (Hz)	125	250	500	1000	2000	4000	NRC
30mm ° s	0.26	0.47	0.72	0.97	1.08	1.00	0.80
50 (30mm panel + 20 airgap)	0.31	0.57	0.88	1.12	1.13	0.95	0.95

Choose Your Finish


Select Woodgrain Finish




Select Panel Colorways




Balmoral




The Oaks




Birch




Auchen Flower




Piano Black




Byron Blackbutt




Glen Rowan




Toorak



Birchgrove




Blackheath



Ashgrove

Mounting Methods

Construction adhesive



Pot Magnet Install

