



Timbertop

Perforate FilaSorb™

acoufelt
making quiet

Distributed by



Product Detail

Product	Timbertop
Surface	Wall and ceiling
Composition	Polyester + Wood Veneer
Material	FilaSorb™
Recycled content	60% min
Weight	4800g/m ² +/- 10%
Size	1200 x 2800mm
Thickness	13mm +/- 10%
	31mm +/- 10%

Guarantees

FilaSorb™	
Warranty against defects	20 Years*
Light fastness warranty	20 Years*
	*conditions apply

Distributed by



NSW
65A Stephen Road
Botany New South Wales 2019
(02) 9666 6688
sales@grayking.com.au

QLD
(07) 3267 6222
sales@grayking.com.au

Technical Data


Fire Testing	CORE	FACING
	AS ISO 9705 – Group 1, SMOGRA – 7.6m ² /s ²	AS ISO 9705 – Group 2
13mm	EN 13501-1 – B-s1, d0	
31mm	AS ISO 9705 – Group 1, SMOGRA – 5.8m ² /s ²	AS ISO 9705 – Group 2
Indoor Air Quality	Low VOCs emission, formaldehyde and Phenol-free	
Light Fastness (FilaSorb™)	ISO 105-B02 1994, 6-7	

Environmental Attributes

- Recognised under LEED
- Minimum 60% recycled PET



Acoustic Performance



Frequency (Hz)	125	250	500	1000	2000	4000	NRC
12mm α _s	0.06	0.02	0.23	0.61	0.89	0.95	0.45
12mm α _s 20mm air gap	0.03	0.14	0.33	0.74	1.00	1.00	0.54
30mm α _s	0.26	0.47	0.72	0.97	1.08	1.00	0.80
50 (30mm panel + 20 airgap)	0.31	0.57	0.88	1.12	1.13	0.95	0.95



Colorways



Crem Oak



Ribbon Oak



Salt Gum Tweed



Lamora



Silver Strata




Possum Birch




Murray Walnut



Teak



Smokey Oak



Classic Ebony